

# flowvess

PWF-V Expansion Vessel

#### DATA SHEET

First Publication Date: 01/09/2020

Revision: ∨¹ Revision Date:







### PRODUCT OVERVIEW

Flowvess PWF-V Range

The **flow**vess PWF-V potable water expansion vessels for use in domestic or commercial sealed chilled and hot water systems.

A wide range of sizes from 2 to 1000 litres. The Flowvess PWF-V expansion vessels are made of top-quality steel and epoxy powder coated in (RAL 9006) aluminium colour, the vessel incorporates a unique contoured, replaceable bladder.

Suitable for flow temperatures up to 100°C and addition of glycol-based anti-freeze up to 50%.

Materials for use in potable water systems must also be absolutely hygienic. In this regard, the following aspects play a part:

- 1 Protection of human health.
- 2 Possible transfer of smell and taste to the potable water.
- 3 Release of (harmful) substances into the potable water.

These aspects cannot be considered in isolation. Apart from the materials used, the design of the vessel, the membrane installed and even the production method of the vessels play an important part.

- Maximum Working Pressure: 10 bar Rated
- Capacity: 2 1000 litre
- Maximum operating temperature: 100°C
- Suitable for addition of glycol-based anti-freeze up to 50%.
- Each vessel is factory tested.
- Nitrogen gas filling for longer retention of pre-charge.

## MODELS & DIMENSIONS DATA

MODEL	Litres	ØD	н	Connection	Weight Kgs
flowvess PWF-V 2	2	120	235	1/2"	1.15
flowvess PWF-V 3	3	170	240	3/4"	1.5
flowvess PWF-V 5	5	170	275	3/4"	1.7
flowvess PWF-V 8	8	220	305	3/4"	2.2
flowvess PWF-V 12	12	260	310	3/4"	2.9
flowvess PWF-V 16	16	260	345	3/4"	3.4
flowvess PWF-V 18	18	260	375	3/4"	3.5
flowvess PWF-V 24	24	260	485	3/4"	4.3
flowvess PWF-V 35	35	380	470	1"	8.0
flowvess PWF-V 50	50	380	720	1"	9.9
flowvess PWF-V 60	60	380	830	1"	12.1
flowvess PWF-V 80	80	460	860	1"	14.0
flowvess PWF-V 100	100	460	880	1"	16.0
flowvess PWF-V 150	150	510	1030	1"	25.5
flowvess PWF-V 200	200	590	1070	1 1/4"	37.5
flowvess PWF-V 300	300	650	1250	1 1/4"	50.5
flowvess PWF-V 500	500	750	1600	1 1/4"	86
flowvess PWF-V 750	750	800	1820	2"	153
flowvess PWF-V 1000	1000	800	2130	2 1/2"	183

All dimensions in mm

## DIMENSIONAL DRAWINGS & SCHEMATICS







## **flow**zone<sup>®</sup>

MEMBERS AREA

This section of the **flow**tech® website holds information exclusively for members. Members will need to log in to gain access to these pages.

Our member's will be granted exclusive access to our **flow**view<sup>®</sup> technical resource library. Within this resource is a wide range of product information including data sheets, technical drawings, O&M Manuals and training videos



### **flow**care<sup>®</sup>

AFTER SALES SERVICE

At **flow**tech® we operate a network of Service Engineers located throughout the UK who are supported by our offices located in Greater Manchester. The distribution of engineers means that in the majority of cases we are less than 4 hours away from attending a customer call out.

We place great emphasis on providing technical back up to support our Service Engineers in resolving some difficult operational and technical issues. We pride ourselves on completing a project on time, within budget and never leaving a problem unresolved, or a customer waiting. This quality of service has made us the first choice for our customers.

FOR FURTHER INFORMATION OR ASSISTANCE

#### contact us

Flowtech Water Solutions are experts in water services and water booster sets. We have continuously supplied a wide range of standard and custom products since being founded in 1996.

#### **MANUFACTURE & SUPPLY**

**TELEPHONE**: 0333 200 1756

EMAIL: info@flowtech.org.uk

#### **SERVICE & MAINTENANCE**

**TELEPHONE**: 0333 200 1813

EMAIL: service@flowtech.org.uk

WEBSITE: www.flowtech.org.uk

ADDRESS: Unit 1 Lock Flight Buildings, Wheatlea Industrial Estate,

Wigan, Greater Manchester WN3 6XP United Kingdom

